





## Kylskål SKS



Isolerskål av polyuretan inklusive rörklamma med mutter för gäng-Stång.

Termisk cond: 0,042 W/mK vid 10 ° C  
 Densitet: 250 kp/m<sup>3</sup>  
 Tryckhållfasthet: 0,7 N/mm<sup>2</sup>  
 Brandklass: B2  
 Temp.best: -50° C - + 110° C



Artikel nr	Dimension	För rör	Y.d mm	Isolering mm	B mm	Förp
26700	17/20	3/8"	17	40 x 20	102	50
26702	18/20		18	40 x 20	103	50
26704	21/20	1/2"	21	40 x 20	106	50
26706	22/20		22	40 x 20	106	50
26708	27/20	3/4"	27	40 x 20	115	50
26710	28/20		28	40 x 20	115	50
26712	33/20	1"	33	40 x 20	120	50
26714	35/20		35	40 x 20	120	50
26716	42/30	1 1/4"	42	40 x 30	149	25
26718	48/30	1 1/2"	48	40 x 30	150	25
26720	57/30		57	40 x 30	165	25
26722	60/30	2"	60	50 x 30	165	25
26724	70/30		70	50 x 30	176	25
26726	76/30	2 1/2"	76	50 x 30	176	25
26728	89/30	3"	89	50 x 30	196	25
26730	108/40		108	60 x 40	248	10
26732	114/40	4"	114	60 x 40	252	10
26734	133/40		133	60 x 40	272	10
26736	139/40	5"	139	60 x 40	275	10
26738	159/40		159	60 x 40	303	10
26740	168/40	6"	168	60 x 40	307	10
26742	219/60	8"	219	100 x 60	405	10
26744	273/60	10"	273	100 x 60	460	10
26746	324/60		324	100 x 60	506	10

Ej lagervara: Leveranstid ca: 1-2 arbetsveckor

3/8" - 3" : M 16/M 10/M 8  
 108 - 168: 3/8"/M 12/M 10  
 8" - 324 : 1/2"/M 16/M 12

